

Mail.XML 16.0 Technical Specification

MID-CRID

September 12, 2014

Prepared by United States Postal Service

Release Version Support

This document contains information pertaining to Mail.XML release version 16.0 and the following USPS *PostalOne!* Releases:

- Release 38 August 2014
- Release 39 November 2014

Technical Support from the USPS Help Desk and Tier 2 Support:

The USPS provides Mail.XML technical support for mailers/vendors and support is only specific to the business rules it pertains to implementation of business transactions, error codes/descriptions and exception handling with the Mail.XML implementations.

The USPS does not provide nor is it equipped to provide technical support for software development tools or IDEs (Integrated Development Environments) like Visual Studio, and software development related activities as they pertain to different technology specific programming environments for different companies, such as .Net, Java, Visual Basic, Power Builder, C, C++ etc.

The Mailer/Vendor is responsible for obtaining technical support and assistance directly from the IDE vendor such as Microsoft, IBM or Sun/Oracle for software development related help needs.

Trademarks

The following trademarks are owned by the United States Postal Service:

ACS™, CASS™, CASS Certified™, Certified Mail™, DMM®, FAST®, First-Class™, First-Class Mail®, Full-Service ACS™, IM®, IMb™, IMb Tracing™, Intelligent Mail®, OneCode ACS®, OneCode Solution®, PLANET Code®, *PostalOne!*®, POSTNET™, Postal Service™, Priority Mail®, Registered Mail™, RIBBS™, Standard Mail®, The Postal Service®, United States Postal Service®, USPS®, USPS.COM®, ZIP®, ZIP Code™, ZIP + 4® and ZIP+4™.

IDEAlliance and Mail.dat are registered trademarks of the International Digital Enterprise Alliance, Inc. (IDEAlliance).

Sun, Sun Microsystems, and Java are trademarks or registered trademarks of Sun Microsystems, Inc.

Microsoft, Microsoft Windows, and Microsoft Internet Explorer are registered trademarks of Microsoft Corporation.

All other trademarks used are the property of their respective owners.

TABLE OF CONTENTS

| Table of Contents | i |
|--|----|
| Document Change History | iv |
| 1. Postal Service Mail.XML | |
| 1.1 Overview | 1 |
| 1.2 Purpose | 1 |
| 1.2.1 Document Scope | 1 |
| 1.3 Intended Audience | 1 |
| 1.4 Mail.XML | 1 |
| 1.5 Roadmap of Mail.XML | 2 |
| 1.6 General XML and Web Services Information | 2 |
| 1.7 Environments Supported by USPS | 2 |
| 1.8 PostalOne! WSDL Information | 3 |
| 1.9 Profiles Management Features | 3 |
| 2. MID and CRID Application Process | 5 |
| 2.1 Requesting CRIDs using Mail.XML Web Services | |
| 2.1.1 Preconditions: | |
| 2.1.2 Process: | |
| 2.1.3 USPS CRID Create Request Overview | |
| 2.2 Requesting MIDs using Mail.XML Web Services | |
| 2.2.1 Preconditions: | |
| 2.2.2 Process: 2.2.3 USPS MID Create Validate Request | |
| 3. MID and CRID Mail.XML Messages Overview | |
| 3.1 Overview | |
| 3.2 Profile Management Messages Workflow | |
| 3.3 Exceptions | |
| 3.4 Fault Codes | |
| 3.5 MID and CRID Error/Return Codes | |
| 4. Data Structure and Business Rules for Mail.XML 16.0 Specification | |
| 4.1 USPSMIDCreateValidateRequest | |
| 4.2 USPSMIDCreateValidateResponse | |
| 4.3 USPSCRIDCreateValidateRequest | |
| 4.4 USPSCRIDCreateValidateResponse | |
| · | |
| 5. Mail.XML 16.0 Complex and Attribute Groups Definitions | |
| 5.1 Complex Type: AddressType | |
| 5.2 Complex Type: basicReturnInfo | 20 |

| | 5.3 Complex Type: CRIDCreateResponseType | 20 |
|----|---|----|
| | 5.4 Complex Type: CRIDEntryType | 21 |
| | 5.5 Complex Type: CRIDsRequestedType | 21 |
| | 5.6 Complex Type: CRIDQueryResponseType | 21 |
| | 5.7 Complex Type: CRIDValidateResponseType | 22 |
| | 5.8 Complex Type: ForeignAddressType | 22 |
| | 5.9 Complex Type: LegalAknowledgmentBlockCRIDType | 22 |
| | 5.10 Complex Type: LegalAknowledgmentBlockMIDType | 27 |
| | 5.11 Complex Type: LegalAknowledgmentBlockMSPSType | 32 |
| | 5.12 Complex Type: MIDCreateResponseType | 36 |
| | 5.13 Complex Type: MIDEntryType | 37 |
| | 5.14 Complex Type: MIDQueryResponseType | 37 |
| | 5.15 Complex Type: MIDType | 38 |
| | 5.16 Complex Type: MIDValidateResponseType | 38 |
| | 5.17 Complex Type: permitPublicationDataType | 38 |
| | 5.18 Complex Type: SubmittingParty, participantIDType | 39 |
| | 5.19 Complex Type: SubmittingSoftware | 39 |
| | 5.20 Complex Type: VerificationErrorType | 39 |
| 6. | Simple Types Data Structure | 40 |
| | 6.1 simpleType: CRIDStatusType | |
| | 6.2 simpleType: CRIDType | |
| | 6.3 simpleType: EnrollingForSelf | 40 |
| | 6.4 simpleType: mailerID6Type | 40 |
| | 6.5 simpleType: mailerID9Type | 40 |
| | 6.6 simpleType: MIDorCRIDRequestType | 40 |
| | 6.7 simpleType: mIDStatusType | 40 |
| | 6.8 simpleType: ns04 | 40 |
| | 6.9 simpleType: ns05 | 40 |
| | 6.10 simpleType: ns09 | 41 |
| | 6.11 simpleType: permitTypeType | 41 |
| | 6.12 simpleType: s12 | 41 |
| | 6.13 simpleType: s40 | 41 |
| | 6.14 simpleType: s50 | 41 |
| | 6.15 simpleType: s64 | 41 |
| | 6.16 simpleType: s255 | 41 |
| | 6.17 simpleType: s260 | 42 |
| 7. | WSDL Reference Information | 43 |
| | Change History Archives | |
| ĸ | Change History Archives | 44 |

| Index | А |
|-------|---|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

DOCUMENT CHANGE HISTORY

Change History of previous versions may be found in the Change History Archive, Section 8.

These are the changes to Mail.XML MID-CRID 16.0-R18 Edition 4 Change 2

| Date | Section # | Title | Description |
|---------|-----------|----------------------------------|--|
| 9/11/14 | 5.8 | Complex Type: foreignAddressType | Removed City, Province, CountryName, and PostalOrZipCode from foreignAddressType per data dictionary |
| 9/11/14 | 4.1 | USPSMIDCreateValidateRequest | Updated business rules description of foreignAddressType to remove City, Province, CountryName, and PostalOrZipCode from per data dictionary |
| 9/11/14 | 4.3 | USPSCRIDCreateValidateRequest | Updated business rulesdescription of foreignAddressType to remove City, Province, CountryName, and PostalOrZipCode from per data dictionary |

These are the changes to Mail.XML MID-CRID 16.0-R18 Edition 4 Change 1

| Date | Section # | Title | Description |
|--------|-----------|-------|--|
| 9/3/14 | Various | N/A | Corrected version references from Mail.XML 16.0A to Mail.XML 16.0 (Errata "A" was still referenced in a few sections.) |

These are the changes to Mail.XML MID-CRID 16.0-R18 Edition 4 Change 0

| Date | Section # | Title | Description |
|---------|-----------|----------|---|
| 8/25/14 | Various | N/A | Updated cover page, footer to reflect Edition 4 publication date. |
| 8/27/14 | 1.4 | Mail.XML | Updated hyperlink |

1. Postal Service Mail.XML

1.1 Overview

The document describes the Mail.XML messages that can be used to apply for Mailer IDs (MIDs) or Customer Registration IDs (CRIDs) electronically for mailers and mail owners.

1.2 Purpose

The purpose of this Technical MID/CRID document is to supplement the Postal service Mail.XML technical guide for Data Distribution and profiles, so that specific focus can be given to the MID and CRID application process.

1.2.1 Document Scope

This document is divided into following sections:

- Section 1.0 provides an overview of the Mail.XML and also states the purpose of this document.
- Section 2.0 provides an overview of the Profile Management functionalities for MID and CRID application
- Section 3.0 provides an overview of MID and CRID Mail.XML Messages.
- Section 4.0: This section provides technical information (Data Structure and Business Rules) for all messages supported in 16.0 specifications

1.3 Intended Audience

The intended audiences for this document are technical programmers and technical managers who have prior knowledge of XML language and Mail.dat. The majority of codes used in the Mail.XML base XSD come from the Postal Service Mail.dat specification, which describes the flags used by IDEAlliance.

1.4 Mail.XML

Mail.XML™ is an XML-based IDEAlliance® ((IDEAlliance Mail.XML) specification for Web Services supporting the Services Oriented Architecture (SOA). It is conversational in nature and platform independent. Web Services uses simple HTTP(s) protocol to communicate data over the Internet, thereby bypassing technology-specific restrictions and avoiding network-related security rules. Sound implementations of Web Services provide safe, secure, platform-independent, support near real-time communication, and increase efficiency of conducting business in most business environments.

More importantly, the Mail.XML allows business function-specific communication and faster change management processes with no impact to other service providers/mailing environments within the mailing industry (you can add optional fields or new messages without requiring every software in the mailing supply chain to change), which has been a core improvement area for the Mail.dat[®] specification. Mail.XML is a complement to Mail.dat, customers using Mail.dat can continue to use it as a database, and can use Mail.XML for communication, automation of business to business processing, and getting answers in near real time from their business partners including the USPS.

The Mail.XML 16.0 functionality provides four major business functions: eDoc messages, data distribution messages, profile management messages, and FAST scheduling messages. The focus of this document is profile management messages.

The IDEAlliance Mail.XML version 16.0 specification is composed of families of related messages that provide all the capability that Mail.dat specification provided, as well as business function support that Mail.dat did not provide. Business functions supported include ability to request data on Customer Registration ID (CRID), and Mailer ID (MID). The specification also provides the mailing industry to conduct many business functions through near real-time communication mechanisms specifically to support joint scheduling and transportation management communications.

All business functions supported by the USPS as part of the Mail.XML implementation are based upon SOA. With this architecture, the mailer's software manages the data transactions for query, create, update, and cancel business functions, as well as subscription models. Additionally, mailer's software is able to receive synchronous and asynchronous transactions through Web Services protocol from the USPS in support of the just-in-time communication architecture.

1.5 Roadmap of Mail.XML

Table 1-1 shows version support of Mail.XML for Profiles Management through November 2014.

| October 2013 | January 2014 | August 2014 | November 2014 |
|--|--|---|---|
| Release 36.0 | Release 37.0 | Release 38.0 | Release 39.0 |
| Mail.XML 12.0A Mail.XML 12.0B Mail.XML 14.0A | Mail.XML 12.0A Mail.XML 12.0B Mail.XML 14.0A | Mail.XML 12.0A Mail.XML 12.0B Mail.XML 14.0A Mail.XML 16.0** | Mail.XML 12.0A Mail.XML 12.0B Mail.XML 14.0A Mail.XML 16.0 |

Table 1-1 Roadmap of Mail.XML supported versions per release

Note: The version(s) flagged with a single asterisk (*) are version(s) currently planned for decommission with the release date.

Note: The version(s) flagged with a double asterisk (**) are new version(s) which are planned for implementation with the release date.

Table 1-2 lists all Mail.XML Profiles Management messages for MIDs and CRIDs supported by Mail.XML 16.0.

| Message | Supported in Mail.XML 16.0 |
|--------------------------------|----------------------------|
| USPSCRIDCreateValidateRequest | X |
| USPSCRIDCreateValidateResponse | X |
| USPSMIDCreateValidateRequest | X |
| USPSMIDCreateValidateResponse | X |

Table 1-2 Profiles Management Messages List for Mail.XML 16.0 Version

1.6 General XML and Web Services Information

XML

XML stands for eXtensible Markup Language. It is used to transport and store data. For general information on XML, visit XML Tutorial.

XSD

An XSD is the XML Schema that describes the structure of an XML document. For general information on XSD visit XML Schema Tutorial.

Web Service

A Web Service is a feature that converts your software into an internet-based software and publishes its functions/message to the users of the internet. For general information on Web Services visit:

Web Services Tutorial

WSDL Tutorial

SOAP Tutorial

1.7 Environments Supported by USPS

The USPS supports two environments for electronic file submissions: the Testing Environment for Mailers (TEM) and the Production environment.

TEM: This environment is used for authorization for all mailers prior to moving into the production environment. Mailers work with the help desk to start the approval process for their software, and will be approved, where appropriate, in the TEM environment prior to sending Mail.XML data transactions in the production environment. The CRID and MID requests in the TEM environment utilize test data. Data entered for CRID and MID requests will impact the production data. Therefore it is requested that only a few CRID and a few MID requests be processed.

Production environment: This environment is used by all customers that have been approved in the TEM to send transactions/messages.

1.8 PostalOne! WSDL Information

All Web Services transactions that are made with the USPS should comply with the WSDL specification that are posted on RIBBS[®] and can be downloaded from the following location: Web Service Description Language (WSDL) Specification.

A Web Services request must include a valid and active USPS User ID and Password as defined in the UserAuthenticationInfo.xsd file that is provided as part of the WSDL downloadable files. A typical web service message construct is defined is as follows:

```
<wsdl:message name="DeliveryApptContentUpdateRequest">
    <wsdl:part name="authInfo" element="auth:AuthenticationInfo"/>
    <wsdl:part name="apptContentUpdate" element="tns:apptContentUpdate"/>
</wsdl:message>
```

With the following:

XSD-typed WSDL:

```
<wsdl:message name="FullServiceStartTheClockQueryRequest">
   <wsdl:part element="uspsmxml:FullServiceStartTheClockQueryRequest"
   name="FullServiceStartTheClockQueryRequest"/>
   </wsdl:message>
```

USPS will validate and authenticate the user information before processing the request. An error message will be returned in response to the web service request for invalid user information.

Message Types WSDL

The USPS only supports the Message-Type WSDL. The following paragraphs describe the Message-Type WSDLs:

The Message-Type eliminates the need to manually register each service and Message-Type. With this method, customers can use an automated tool that can set up their environment without manually registering each service. However, this approach requires updates to WSDLs every time a new Mail.XML version is released. In other words, it is tightly coupled with the Mail.XML Specification Version. The USPS has transitioned to this type of Message WSDLs to remove manual editing and registering of messages.

The customer must use a message-type URL to engage the services. These URLs are provided in the WSDLs and XSDs section of this document..

1.9 Profiles Management Features

- Implementation of the USPS.com Style Sheet
- The ability to apply a Data Distribution Profile to multiple MIDs
- The ability to delegate editing or adding of a Full Service Address Change Service (ACS) billing profile to another Customer Registration Identification (CRID)
- The ability to set the default available MID count to 2 instead of 1
- A Mailer ID Tool (external facing pages) assumes the style sheet of the USPS.com look and feel from the Phoenix project.
- The ability for external users to manage their Data Distribution profiles in bulk.
- Once users submit a new or updated Data Distribution profile for a given CRID, the MID system prompts them to ask if they would like to apply the same Data Distribution profile information to other MIDs in his profile.
- If a user chooses to apply the Data Distribution profile information to other MIDs to be the recipient of the new or
 edited Data Distribution profile, the MID system allows the user to select one or any combination of MIDs
 associated with the user's CRID.
- Enables the user to apply Data Distribution profile information (one or any combination) of MIDs associated with the user's CRID. The MID system also allows the user to select all MIDs.
- Allows the user to delegate a CRID to have the ability to edit or add a Full Service ACS billing profile. In that scheme, all MIDs linked to the CRID have the same Full Service ACS billing profile.

The section for MID selection in the MID system contains the following fields:

- MID
- Customer Reference

MID Assignment

External users are allowed to request two MIDs without the system performing volume checks. Users are also able to request additional MIDs above the volume allotment.

Mailing Agents (or other third party, Mail Services Providers (MSPs)) are allowed to request MIDs on behalf of their clients or mail owners.

Furthermore, the MID system allows a user to request up to two MIDs before it verifies mailing volumes.

2. MID and CRID Application Process

This section covers the process for the creation of CRIDs and MIDs.

Note 1: In order to use the USPS Web Services in the production environment all users must first complete the testing in the USPS TEM environment.

Note 2: It is recommended that no more than 20 CRIDEntry elements be specified in the USPSCRIDCreateValidateRequest message, and no more than 2 MIDEntry elements be specified in the USPSMIDCreateValidateRequest message. If the systems are not able to process the request within ten (10) seconds, a fault response is returned to the user with a Tracking ID that the user can use to retrieve the response at a later time.

2.1 Requesting CRIDs using Mail.XML Web Services

This section describes the CRID request process using Mail.XML. The section covers those who wish to request for multiple CRIDs in one message.

Note: The MID and CRID Mail.XML requests are processed using the USPS production systems. Therefore, it is very important that the CRID and MID testing scenarios are successfully executed only one time. In order to avoid performance related issues, the Postal Service recommends that the CRID request sent in TEM or Production environment should have no more than twenty (20) CRID requests grouped in one message.

2.1.1 Preconditions:

- 1. Review the TEM approval guide "Full-Service Data Feedback Authorization Guide for Mail.XML" located at RIBBS. This guide covers testing scenarios for the CRID and MID generation. Users are required to fill out the Survey form to identify that they wish to test CRID/MID functionality. Completing the survey forms will also initiate the process of mailer/user activation in the TEM (Test environment). Successful tests must be performed in the TEM environment in order to initiate activation in the production environment.
- 2. When testing in the TEM environment, users should generate requests for CRIDs using test data. The CRIDs generated in the TEM environment are also transmitted to the production environment. Company names that are made up and addresses that do not belong to that facility should be used as test data. Note that the addresses for the CRIDs are matched against the USPS Address Management System Database (AMS) system; therefore, for the CRID request to work the addresses must be real addresses.
- 3. When requesting CRIDs in the production environment, correct Company names and correct corresponding addresses should be used.
- 4. The requester will need one CRID and a Business Customer Gateway account to send this request.
- 5. The CRIDs can be requested for one's own organization, as well as, for a partner. The Mail.XML message requires the submitter to inform USPS if the request is "ApplyingForSelf" as a Yes or No indicator. Yes is translated as the request is for one's own organization, and No is translated as the request is for one's partner. In case No is selected, the Mail.XML Legal Acknowledgement block becomes required and submitter/agent must provide the full legal acknowledgement statement as defined in the sections below.

2.1.2 Process:

This section provides an overview of the CRID request process. For detailed technical specifications and to identify the exact data format and elements for the required fields, please review the sections "Data Structure and Business Rules for Mail.XML".

- 1. Compile the list of addresses for the CRID with the required information as provided in this guide. For more information please review the section Prerequisites above.
- 2. Convert the list into compatible Mail.XML XSD verified form.
- 3. It is highly recommended that the requester sends only twenty (20) CRID addresses in one request. Multiple requests can be sent one after the other. For testing in the TEM environment we request that only one successful CRID USPS CRID Create Validate Request be processed, as the CRIDs get transmitted to the Production environment. As for production multiple CRID USPS CRID Create Validate Requests can be sent as needed, with no more than twenty (20) CRID requests in each.

2.1.3 USPS CRID Create Request Overview

Please refer to the USPSCRIDCreateValidateRequest section in this document for details on the required fields and the business logic. Table 2-1 contains a snapshot of this Mail.XML message; more details are listed in the following sections.

| Field | Sub Field | Format | Required |
|---------------------|--------------------------------|-----------------------|---|
| SubmittingParty | | | Required for system |
| Submitting Software | | | Required for system |
| CRIDEntry | | | |
| | Company Name | String 255 | Required |
| | Permit Publication Data | | Optional |
| | Company HQ Indicator | Yes or No simple type | Optional |
| | Address | | Required |
| | Address Match | Yes or No | Required |
| | Applying For Self | Yes or No | Required |
| | Legal Acknowledgement Block | | Conditional; required if ApplyingForSelf is set to "No" |

Table 2-1 USPS CRID Create Request Overview

2.2 Requesting MIDs using Mail.XML Web Services

This section covers the MID request process using Mail.XML. This section is written to support mailers/users who wish to request many MIDs at the same time.

Note: In order to avoid performance related issues, the Postal Service recommends that the MID request sent in TEM or Production environment should have no more than two (2) MIDEntry requests grouped in one message.

2.2.1 Preconditions:

- 1. Review the TEM approval guide "Full-Service Data Feedback Authorization Guide for Mail.XML" located on RIBBS. This guide covers testing scenarios for the CRID and MID generation. Users are required to fill out the survey form to identify that they wish to test CRID/MID functionality. Completing the survey forms will also initiate the process of mailer/user activation in the TEM (Test environment). Successful tests must be performed in the TEM environment in order to initiate activation in the production environment.
- 2. When testing in the TEM environment, users should generate requests for MIDs using test data. The MIDs generated in the TEM environment are also transmitted to the production environment. Company names that are made up and addresses that do not belong to that facility should be used as test data. Note that the addresses for the MIDs are matched against the USPS Address Management System Database (AMS) system; therefore, for the MID request to work the addresses must be real addresses.

When requesting MIDs in the production environment, correct company names and correct corresponding addresses should be used.

- 3. The requester will need one MID and a Business Customer Gateway account to send this request.
- 4. The MIDs can be requested for one's own organization, as well as for a partner. The Mail.XML message requires the submitter to inform USPS if the request is "ApplyingForSelf" via use of a Yes or No indicator. Yes is translated as meaning the request is for one's own organization, and No is translated as meaning the request is for one's partner. In case No is selected, the Mail.XML Legal Acknowledgement block becomes required and submitter/agent must provide the full legal acknowledgement statement as defined in the sections below.

2.2.2 Process:

This section provides an overview of the MID request process. For detailed technical specifications and to identify the exact data format of the required fields, please review the sections "Data Structure and Business Rules for Mail.XML".

1. Compile the list of MID information and addresses with the required information as provided in this guide.

Note: In the TEM environment only dummy addresses and dummy company names must be used. You must not use real data in TEM as it will cause that data to be transmitted to the production CRID / MID system.

- 2. Convert the list into compatible Mail.XML XSD verified form.
- 3. It is highly recommended that the requester sends only two (2) MID addresses in one Mail.XML USPS MID Create Validate Request message. Multiple MID requests can be sent one after the other. For testing in the TEM environment USPS requests that only one successful USPS MID Create Validate Request be processed, as the MIDs get transmitted to the Production environment. In the production environment, multiple USPS MID Create Validate Request can be sent as needed, with no more than two (2) MID requests in each.

2.2.3 USPS MID Create Validate Request

This section contains details on the required fields and the business logic. Table 2-2 contains a snapshot of this Mail.XML message.

| Field | Sub-Field | Format | Required |
|--------------------|------------------------------|---|---|
| SubmittingParty | | | Required |
| SubmittingSoftware | | | Required |
| MIDEntry | | | Required |
| | CustomerCRID | CRIDType simple type | Required |
| | CustomerName | String 40 | Required |
| | PermitPublicationData | | Optional |
| | CompanyHQIndicator | Yes or No simple type | Optional |
| | Address | | Required |
| | SequenceNumber | integer | Optional |
| | ApplyingForSelf | yesNo simple type | Required |
| | LegalAcknowledgment Block | legalAcknowledgementBloc kMIDType complex type | Conditional; required if ApplyingForSelf is set to "No" |

Table 2-2 Snapshot of the Mail.XML message

3. MID and CRID Mail.XML Messages Overview

3.1 Overview

As part of the Mail.XML 16.0 Web Services messages, USPS will allow mailers with the capability to manage their corporate identification.

Table 3-1 contains the list of messages supported in Mail.XML 16.0 Specification with their description and details on each of these messages:

| Message Name | Message Description |
|--------------------------------|---|
| USPSMIDCreateValidateRequest | This message will allow Mailers to request the <i>PostalOne!</i> System to create the Mailer ID (MID), if one already exists, USPS responds with the existing MID. |
| USPSMIDCreateValidateResponse | This is a response message that notifies the requestor whether the request for creating the MID has been accepted or rejected. If the request is accepted than the MID will be sent back to mailer in the response message |
| USPSCRIDCreateValidateRequest | This message will allow mailers to request the <i>PostalOne!</i> System to create the CRID for their corporation, if one already exists, USPS responds with the existing CRID. |
| USPSCRIDCreateValidateResponse | This is a response message that informs the requestor whether the request for creating the CRID has been accepted or rejected. If the request is accepted than the CRID will be sent back to the mailer in the response message |

Table 3-1 Profile Management Messages Supported in Mail.XML 16.0

3.2 Profile Management Messages Workflow

All messages in Profile Management families follows Pull method where user sends a request and expects to receive a response whether with the data or error/return code that is returned to the user.

There is no order by which user must request or send messages. User can request CRID or MID creation messages without any order.

3.3 Exceptions

The following table contains the exceptions identified by the USPS.

| Mail.XML Version | Exception Description |
|-----------------------------|---|
| 12.0A,12.0B, 14.0A, 16.0 | The customer should not zero-pad their MID and CRID IDs |

Table 3-2 List of exceptions identified by USPS

3.4 Fault Codes

Faults, such as a message timeout or invalid XML are to be communicated using the fault element and returned within the detail section of the SOAP fault. The fault is made up of a tracking ID and one or more fault codes and optional fault descriptions. Note all of the Error/Return Codes listed below are supported in Mail.XML 16.0.

Table 3-3 contains the list of fault codes that are applicable to all Mail.XML messages, they are sent whenever a fault occurs in the transmission of the message.

| Code | Description | Action* | Messages | Severity |
|------|-------------------------|--|----------------------------------|----------|
| 401 | Incomplete/Cannot Parse | Please submit the request again | Fault (All Mail.XML | Error |
| | · | with well-formed XML according to XSD. | Messages) | |
| 402 | Not Well Formed XML | Please submit the request again with well-formed XML according | Fault (All Mail.XML Messages) | Error |
| | | with wen formed Aivie according | wicoodycoj | |

| Code | Description | Action* | Messages | Severity |
|-------------------|---|---|-----------------------------------|-------------|
| | | to XSD | | |
| 403 | Request XML is invalid against the XSDs | Please submit the request again with well-formed XML according to XSD. | Fault (All Mail.XML Messages) | Error |
| 412 | Invalid user | Please submit the request again with a valid user. | Fault (All Mail.XML Messages) | Error |
| 440 | Sorry - MailXML version is not supported | version is not Please submit the request again with MailXML version supported by PostalOne Data Distribution System. Fault (All Mail.XML Messages) Messages) | | Error |
| 500 | Mail.XML generic internal error | Please contact PostalOne! Help Desk. | Fault (All Mail.XML Messages) | Error |
| 501 | MailXML request is missing 'SubmitterTrackingID' which is required for processing the Message | Please submit the request again with SubmitterTrackingID. | Fault (All Mail.XML Messages) | Error |
| 502 1 | Duplicate submitter ID. This Mail.XML request for Message #messageName# with SubmitterTrackingID #submitterTrackingID# was not processed by Mail.XML application because an identical request was received on #submitDate# and was assigned TrackingID of #trackingID#. | Please use the MRRR message with Tracking ID #trackingID# to retrieve. | Fault (All Mail.XML Messages) | Error |
| 503 | Not Implemented - MailXML message received is not supported | Please submit the request again with MailXML message supported by PostalOne Data Distribution System. | Fault (All Mail.XML Messages) | Error |
| 505 ¹ | Submitter tracking ID is too long | Please submit the request again with SubmitterTrackingID length not exceeding the length specified in the Tech Spec. | Fault (All Mail.XML Messages) | Error |
| 1500 | Invalid tracking ID | Please submit the request again with a valid Tracking ID. | Fault (All Mail.XML Messages) | Error |
| 1502 ² | Come Back Later | The response is not available at this time, Please try again later. | Fault (All Mail.XML Messages) | Warning |
| 1502 | Come Back Later | The response is not available at this time, Please try again later. | MessageResponseRetr ievalResponse | Warning |
| 1510 | The TrackingID provided in the MessageResponseRetrievalResponse request was processed by Mail.XML application on #processedDate#. No response was received by Mail.XML from the target application. | Please submit the request again or contact PostalOne! Help Desk. | Fault (All Mail.XML Messages) | Information |
| 1600 | MRRR version not matching original request version. | Please submit the MRRR request again using the same MailXML version that was used to submit the original request. | Fault (All Mail.XML Messages) | Error |
| 5101 ³ | Unauthorized - Required SubmittingParty information is empty or missing. | Please submit the request again with valid SubmittingParty block. | Fault (All Mail.XML Messages) | Error |
| 5102 ³ | Unauthorized - User does not have access to specified SubmittingParty. | Please submit the request again with valid SubmittingParty block or contact PostalOne! Help | Fault (All Mail.XML Messages) | Error |

| Code | Description | Action* | Messages | Severity |
|-------------------|--|--------------------------------------|----------------------------------|----------|
| | | Desk. | | |
| 5103 ³ | Unauthorized - User does not have access to 'Manage Mailing Activity' service. | Please contact PostalOne! Help Desk. | Fault (All Mail.XML Messages) | Error |

¹ Error code 501 was used for any Submitter Tracking ID error. In Release 37, Error Codes 502 and 505 are used to enable distinction between Submitter tracking ID errors.

Table 3-3 Fault Codes

3.5 MID and CRID Error/Return Codes

Tables 3-4 and 3-5 contain the list of the return codes that the *PostalOne!* system will communicate to the customer in response to the MID/CRID Create validate request messages to indicate the success or the failure of the request. These error/return codes are applicable to Mail.XML 16.0 versions.

| Code | Description | Messages |
|------|---|--------------------------------|
| 5000 | FULLSERVICE-EDOC: REQUEST SERVED SUCCESSFULLY. | USPSCRIDCreateValidateResponse |
| 5001 | FULLSERVICE-EDOC: Not Valid Schema. | USPSCRIDCreateValidateResponse |
| 5007 | FULLSERVICE-EDOC: Internal System error message. Please contact <i>PostalOne!</i> Help Desk | USPSCRIDCreateValidateResponse |
| 5008 | FULLSERVICE-EDOC: Empty Message. Please Contact PostalOne! Help Desk. | USPSCRIDCreateValidateResponse |
| 5009 | FULLSERVICE-EDOC: Request is not XML Message. Please Contact <i>PostalOne!</i> Help Desk. | USPSCRIDCreateValidateResponse |
| 5012 | FULLSERVICE-EDOC: 'LegalAcknowledgementBlock' must be specified when 'ApplyingForSelf' is 'No'. | USPSCRIDCreateValidateResponse |
| 5013 | FULLSERVICE-EDOC: 'LegalAcknowledgementBlock > UnderstandLegalLiabilityForApplyingForSomeOneElse' must be 'Yes" when 'ApplyingForSelf' is 'No'. | USPSCRIDCreateValidateResponse |
| 5014 | FULLSERVICE-EDOC: 'LegalAcknowledgementBlock > AcknowledgeNotifyingTheMailOwner' must be 'Yes' when 'ApplyingForSelf' is 'No' | USPSCRIDCreateValidateResponse |
| 5015 | FULLSERVICE-EDOC: The text in the 'USPSLegalAgreement' element does not match the text defined in the Mail.XML specification. | USPSCRIDCreateValidateResponse |
| 5017 | FULLSERVICE-EDOC: The address provided is not a valid USPS address | USPSCRIDCreateValidateResponse |
| 5018 | FULLSERVICE-EDOC: Multiple locations were found for the given address. Please be more specific with the address you provide so that it maps to a single location. | USPSCRIDCreateValidateResponse |
| 5027 | Failure response (non-success status code) received from Customer Registration system. | USPSCRIDCreateValidateResponse |
| 5031 | The Company was not found. | USPSCRIDCreateValidateResponse |
| 5034 | FULLSERVICE-EDOC: CRID cannot be present in the CRIDEntry block for the CRID Create process | USPSCRIDCreateValidateResponse |

² Error Code 500 was used for any generic error and Come Back Later faults. In Release 37, Error Code 1502 is used for any Come Back Later message for consistency.

³ Error Code 412 was used for any User Error. In Release 37, Error Codes 5101, 5102 and 5103 are used to enable distinction between user errors.

^{*} Action tags are only available for Mail.XML specs 14.0A and above.

| Code | Description | Messages |
|------|---|--------------------------------|
| 5035 | FULLSERVICE-EDOC: CompanyName or Address cannot be present in the CRIDEntry block for the CRID Query process. | USPSCRIDCreateValidateResponse |

Table 3-4 CRID Error/Return Codes

| Code | Description | Messages |
|------|---|-------------------------------|
| 5007 | FULLSERVICE-EDOC: Internal System error message Please Contact PostalOne! Help Desk | USPSMIDCreateValidateResponse |
| 5012 | FULLSERVICE-EDOC: 'LegalAcknowledgementBlock' must be specified when 'ApplyingForSelf' is 'No' | USPSMIDCreateValidateResponse |
| 5013 | FULLSERVICE-EDOC: 'LegalAcknowledgementBlock > UnderstandLegalLiabilityForApplyingForSomeOneElse' must be 'Yes' when 'ApplyingForSelf' is 'No' | USPSMIDCreateValidateResponse |
| 5014 | FULLSERVICE-EDOC: 'LegalAcknowledgementBlock > AcknowledgeNotifyingTheMailOwner' must be 'Yes' when 'ApplyingForSelf' is 'No' | USPSMIDCreateValidateResponse |
| 5015 | FULLSERVICE-EDOC: The text in the 'USPSLegalAgreement' element does not match the text defined in the MailXml specification | USPSMIDCreateValidateResponse |
| 5016 | FULLSERVICE-EDOC: The specified 'CustomerCRID' could not be found | USPSMIDCreateValidateResponse |
| 5021 | FULLSERVICE-EDOC: CustomerCRID is required in the MIDEntry block for the MID Create process. | USPSMIDCreateValidateResponse |
| 5022 | FULLSERVICE-EDOC: CustomerCRID or MID is required in the MIDEntry block for the MID Query process. | USPSMIDCreateValidateResponse |
| 5023 | FULLSERVICE-EDOC: Both CustomerCRID and MID cannot be present in the MIDEntry block for the MID Query process. | USPSMIDCreateValidateResponse |
| 5024 | FULLSERVICE-EDOC: All MIDEntry blocks must have CustomerCRID specified or all MIDEntry blocks must have MID specified for the MID Query process. Switching from CustomerCRID to MID is not allowed between MIDEntry blocks. | USPSMIDCreateValidateResponse |
| 5025 | FULLSERVICE-EDOC: CustomerCRID and MID are required in the MIDEntry block for the MID Validate process. | USPSMIDCreateValidateResponse |
| 5027 | Failure response (non-success status code) received from Customer Registration system. | USPSMIDCreateValidateResponse |
| 5028 | Failure response (non-success status code) received from MID system. | USPSMIDCreateValidateResponse |
| 5029 | MID data not found. | USPSMIDCreateValidateResponse |
| 5030 | CRID Data not found. | USPSMIDCreateValidateResponse |
| 5032 | The company was not found. | USPSMIDCreateValidateResponse |
| 5033 | FULLSERVICE-EDOC: CustomerName, CompanyHQIndicator, Address1, Address2, City, State, ZipCode are not allowed when MID is specified. | USPSMIDCreateValidateResponse |

Table 3-5 MID Error/Return Codes

4. Data Structure and Business Rules for Mail.XML 16.0 Specification

The following section identify the business rules and data structure for each of the MID and CRID messages that will be supported in the Mail.XML 16.0 specification.

4.1 USPSMIDCreateValidateRequest

The purpose of this message is to send a request for creating one or more Mailer IDs.

Prerequisites

- Mailer requests the creation of one or more MIDs.
- Mailer passes in the following information at a minimum per MID requested (information must be repeated for each MID requested):
 - o CRID
 - o ApplyingForSelf
- The PostalOne! system will provide feedback to the mailer using USPSMIDCreateValidateResponse Message

If successful:

- Response is returned to mailer
- Response will include per MID requested:
 - o One 9-digit MID if newly created
 - o One or more MIDs if existing

If not successful:

- Response is returned to mailer:
- Response will indicate the problem per MID requested

Business Rules

For each USPSMIDCreateValidateRequest message, the customer needs to provide the information for all of the required blocks.

- Submitting Party
- Submitting Software
- SubmitterTrackingID

The PostalOne! system for each Mail.XML message submitted uses the combination of message name, the SubmitterTrackingID, User ID, and the Mail.XML application generated variables of TrackingID and RequestReceived to check if the message has already been processed in the last 45 days. If the message was already processed then the PostalOne! system shall consider the request as a duplicate request and in this case the system shall send the Response that was processed for the previous request. In this case the system adds a Warning message in the Accept block notifying the submitter that the request was a duplicate request.

The identifier, *SubmitterTrackingID* is part of all Mail.XML Request headers. This SubmitterTrackingID allows for the submitter of the request to uniquely identify one message from the other and to assist with identifying duplicate requests. The system shall handle this process for all Mail.XML Request messages including messages for eDoc, FAST, Data Distribution and MID/CRID generation.

- Customer CRID
- Customer Name (optional)
- Permit Publication Data (optional)
- Company HQ Indicator (optional) The accepted values are 'Yes' or 'No'
- Address Information (optional) Both US and international addresses are supported in the MID Create Request message. Address Information includes the following:

- Address 1
- o Address 2
- o Address 3
- Address 4
- o City
- o County
- o State
- o ZIP Code
- GPS Coordinates
- Urbanization Type
- Foreign Address Foreign Address information includes the following:
 - Address Line 1
 - Address Line 2
 - Address Line 3
 - Country Code
- Sequence Number (optional)
- Applying for Self Indicator. Accepted values are 'Yes' or 'No' Required
- Legal Acknowledgment Required to provide Legal Acknowledgment Block when Applying for Self Indicator is "No." This block requires following info:
 - o UnderstandLegalLiabilityForApplyingForSomeOneElse
 - o AcknowledgementNotifyingTheMailOwner
 - o USPSLegalAgreement

Field Description

| Field | Format | Acceptable Value | Business Rules | Comments |
|--------------------------------------|--------------------------------------|------------------|--------------------|---|
| USPSMIDCreateValidat eRequest BEGINS | | | | |
| SubmittingParty | participantIDType complex type | - | Required | SubmittingParty attributes not required by XSD, but CRID attribute in SubmittingParty is required by application to validate the user Refer to this complex type in Section 5 |
| SubmittingSoftware | submittingSoftwareT ype complex type | - | Required | Refer to this complex type in Section 5 |
| SubmitterTrackingID | String 20 | | Required | Refer to this simple type in Section 6 |
| MIDEntry | midEntryType complex type | - | Required 1 to many | See below for details on midEntryType |
| midEntryType BEGINS | | | | |
| CustomerCRID | CRIDType simple type | - | Required | Refer to this simple type in Section 6 |
| CustomerName | String | | Optional | |

| Field | Format | Acceptable Value | Business Rules | Comments |
|------------------------------------|--|------------------|---|---|
| PermitPublicationData | permitPublicationDa taType complex type | - | Optional | Refer to this complex type in Section 5 |
| CompanyHQIndicator | yesNo simple type | - | Optional | Refer to this simple type in Section 6 |
| Address | addressType complex type | | Optional | Refer to this complex type in Section 5 |
| SequenceNumber | Integer | | Optional | |
| ApplyingForSelf | yesNo simple type | - | Required | Refer to this simple type in Section 6 |
| LegalAcknowledgment Block | legalAcknowledgem entBlockMIDType complex type | - | Conditionally Required when ApplyingForSelf is "No" | Refer to this complex type in Section 5 |
| midEntryType ENDS | | | | |
| USPSMIDCreateValidat eRequest ENDS | | | | |

4.2 USPSMIDCreateValidateResponse

The message is sent by USPS to customer in response to MID Create Validate Request messages.

Prerequisites

- Mailer requests the creation of one or more MIDs.
- Mailer passes in the following information at a minimum per MID requested (information must be repeated for each MID requested):
 - o CRID
 - o ApplyingForSelf
- The PostalOne! system will provide feedback to the mailer using USPSMIDCreateValidateResponse Message

If successful:

- Response is returned to mailer
- Response will include per MID requested:
 - o One 9-digit MID if newly created
 - o One or more MIDs if existing

If not successful:

- · Response is returned to mailer
- Response will indicate the problem per MID requested

Business Rules

Note: The USPSMIDCreateValidateResponse message returns one of the two messages block, i.e., MID Accepted or MID Reject Block.

- In ACCEPT block
 - o Returns all of the data blocks/elements that were sent in the USPSMIDCreateValidateRequest message AND
 - o MID information, which is either MID6 or MID9 AND
 - o OPTIONAL return info block that contains return code and return description
- in REJECT block
 - o Returns all of the data blocks/elements that were sent in the USPSMIDCreateValidateRequest message AND

o REQUIRED return info block that contains return code and return description to communicate the issue

Field Description

| Field | Format | Acceptable Value | Business Rules | Comments |
|---------------------------------------|--|------------------|--|---|
| USPSMIDCreateValidat eResponse BEGINS | | | | |
| TrackingID | String 20 | - | Optional Allows the user to retrieve the data without requiring | |
| SubmitterTrackingID | String 20 | | Required | Refer to this simple type in Section 6 |
| Choice Block BEGINS | | | 1 to many allowed Either Accept or Reject block is returned | |
| USPSMIDCreateAccept Block BEGINS | | | | |
| MID | MIDType complex type | - | Optional | Refer to this complex type in Section 5 |
| MIDStatus | mIDStatus Type simple type | - | Optional | Refer to this simple type in Section 6 |
| MIDEntry | midEntryType complex type | - | Optional | Refer to this complex type in Section 5 |
| RelatedPermitPublicatio nData | mailxml_defs:per mitPublicationDa taType | | Optional | Refer to this complex type in Section 5 |
| ReturnInfo | basicReturnInfo complex type | | Optional | Refer to this complex type in Section 5 |
| USPSMIDCreateAccept Block ENDS | | | | |
| USPSMIDCreateReject Block BEGINS | | | | |
| MIDEntry | midEntryType complex type | - | Required | Refer to this complex type in Section 5 |
| ReturnInfo | basicReturnInfo complex type | - | Required | Refer to this complex type in Section 5 |
| USPSMIDCreateReject Block ENDS | | | | |
| Choice Block ENDS | | | | |
| USPSMIDCreateValidat eResponse ENDS | | | | |

4.3 USPSCRIDCreateValidateRequest

The purpose of this message is to send a request for creating Mailer CRIDs.

Prerequisites

- Mailer requests the creation of one or more CRIDs using USPSCRIDCreateValidateRequest Message.
- Mailer passes the required information per CRID requested
- The PostalOne! system provides feedback to the mailer using USPSCRIDCreateValidateResponse Message

If successful:

- Response is returned to mailer
- Response will indicate whether the included CRID is new or existing

There will always be exactly one CRID returned for a given CRID requested

If not successful:

- Response is returned to mailer:
- Response will indicate the problem per CRID requested

Business Rules

For each USPSCRIDCreateValidateRequest message, the customer needs to provide the information for all of the required blocks.

- Submitting Party
- Submitting Software
- SubmitterTrackingID
- Company Name
- Permit Publication Block (Optional) that must provide information for the following required elements:
 - o Permit Number and PermitZip4 OR
 - o Publication Number
- Company HQ indicator. The accepted values are 'Yes' or 'No'
- Address Information block that must provide information for the required elements. Both US and international
 addresses are supported in the CRID Create Request message. Only AMS matched addresses will be processed
 for CRIDs. Mailers are requested to verify if the addresses are cleansed and can be matched in the AMS system.
 Address Information includes the following:
 - o Address 1
 - o Address 2
 - o Address 3
 - Address 4
 - City
 - County
 - State
 - o ZIP Code
 - o GPS Coordinates
 - Urbanization Type
 - Foreign Address Foreign Address information includes the following:
 - Address Line 1
 - Address Line 2
 - Address Line 3
 - Country Code
- Address Match Indicator. The accepted values are 'Yes' or 'No'
- Applying for Self indicator. The accepted values are 'Yes' or 'No'
- Required to provide Legal Acknowledgment block when Applying for Self Indicator is 'No'. The block requires the following information
 - o UnderstandLegalLiabilityForApplyingForSomeOneElse. The accepted values are 'Yes' or 'No'.
 - o AcknowledgeNotifyingTheMailOwner. The accepted values are 'Yes' or 'No'

o USPSLegalAgreement. This field contains the USPS legal agreement by default.

The *PostalOne!* system for each Mail.XML message submitted uses the combination of message name, the SubmitterTrackingID, User ID, and the Mail.XML application generated variables of TrackingID and RequestReceived to check if the message has already been processed in the last 45 days. If the message was already processed then The *PostalOne!* system shall consider the request as a duplicate request and in this case the system shall send the Response that was processed for the previous request. In this case the system adds a Warning message in the Accept block notifying the submitter that the request was a duplicate request.

The PostalOne! system will implement the new identifier "SubmitterTrackingID" that will be made part of all Mail.XML Request headers. This SubmitterTrackingID allows for the submitter of the request to uniquely identify one message from the other and to assist with identifying duplicate requests. The system shall handle this process for all Mail.XML Request messages including messages for eDoc, FAST, Data Distribution and MID/CRID generation.

Field Description

| Field | Format | Acceptable Value | Business Rules | Comments |
|---------------------------------------|---|---------------------|---|---|
| USPSCRIDCreateValidate Request BEGINS | | | | |
| SubmittingParty | participantIDType complex type | - | Required | SubmittingParty attributes not required by XSD, but SubmittingParty is required by application to validate the user Refer to this complex type in Section 5 |
| SubmittingSoftware | submittingSoftwareType complex type | - | Required | Refer to this complex type in Section 5 |
| SubmitterTrackingID | String 20 | | Required | Refer to this simple type in Section 6 |
| CRIDRequestType | MIDorCRIDRequestType simple type | | Required | Refer to this simple type in Section 6 |
| CRIDEntry | CRIDEntryType complex type | - | Required 1 to many allowed | See below details for CRIDEntryType |
| CRIDEntryType BEGINS | | | | |
| CompanyName | String 255 | | Required | - |
| PermitPublicationData | permitPublicationDataTyp e complex type | - | Optional | Refer to this complex type in Section 5 |
| CompanyHQIndicator | yesNo simple type | - | Optional | Refer to this simple type in Section 6 |
| Address | addressType complex type | - | Required | Refer to this complex type in Section 5 |
| AddressMatch | yesNo simple type | - | Required | Refer to this simple type in Section 6 |
| ApplyingForSelf | yesNo simple type | - | Required | Refer to this simple type in Section 6 |
| LegalAcknowledgementBlo ck | legalAcknowledgementBl ockCRIDtype complex type | - | Conditionally Required when ApplyingForSelf is "No" | Refer to this complex type in Section 5 |
| CRIDEntryType ENDS | | | | |
| USPSCRIDCreateValidate Request ENDS | | | | |

4.4 USPSCRIDCreateValidateResponse

This message is sent by USPS to customer with the CRID number.

Prerequisites

- Mailer requests the creation of one or more CRIDs using USPSCRIDCreateValidateRequest Message.
- Mailer passes the required information per CRID requested
- The PostalOne! system provides feedback to the mailer using USPSCRIDCreateValidateResponse Message

If successful:

- Response is returned to mailer
- Response will indicate whether the included CRID is new or existing
- There will always be exactly one CRID returned for a given CRID requested

If not successful:

- Response is returned to mailer:
- Response will indicate the problem per CRID requested

Business Rules

The USPSCRIDCreateValidateResponse message returns one of the two messages block i.e. MID Accepted or MID Reject Block.

- In ACCEPT block
 - Returns all of the data blocks/elements that were sent in the USPSCRIDCreateValidateRequest message AND
 - o CRID number AND
 - o OPTIONAL return info block that contains return code and return description to communicate the issues
- In REJECT block
 - Returns all of the data blocks/elements that were sent in the USPSCRIDCreateValidateRequest message AND
 - o REQUIRED return info block that contains return code and return description to communicate the issue.

Field Description

| Field | Format | Acceptable Value | Business Rules | Comments |
|--|-----------|------------------|---|--|
| USPSCRIDCreateVali dateResponse BEGINS | | | | |
| TrackingID | String 20 | - | Optional Allows the user to retrieve the data without requiring it. | |
| SubmitterTrackingID | String 20 | | Required | Refer to this simple type in Section 6 |
| Choice Block BEGINS | | | Required 1 to many allowed. Either QueryResults or QueryError block is returned | |
| USPSCRIDCreateAcc ept BEGINS | | | Required | |
| CRID | CRIDType | - | Required | Refer to this simple type in Section 6 |

| Field | Format | Acceptable Value | Business Rules | Comments |
|--------------------------------------|--|------------------|----------------|---|
| CRIDStatus | cRIDStatusType simple type | - | Required | Refer to this simple type in Section 6 |
| CRIDEntry | cridEntryType complex type | - | Required | Refer to this complex type in Section 5 |
| RelatedPermitPublicat ionData | mailxml_defs:permitP ublicationDataType | | Optional | Refer to this complex type in Section 5 |
| ReturnInfo | basicReturnInfo complex type | - | Optional | Refer to this complex type in Section 5 |
| USPSCRIDCreateAcc ept Block ENDS | | | | |
| USPSCRIDCreateRej ect Block BEGINS | | | | |
| CRIDEntry | cridEntryType complex type | | Required | Refer to this complex type in Section 5 |
| ReturnInfo | basicReturnInfo complex type | | Required | Refer to this complex type in Section 5 |
| USPSCRIDCreateRej ect Block ENDS | | | | |
| USPSCRIDCreateVali dateResponse ENDS | | | | |

5. Mail.XML 16.0 Complex and Attribute Groups Definitions

5.1 Complex Type: AddressType

| Field | Format | Acceptable Values | Business Rules | Comments |
|-----------------|--------------------|-------------------|-------------------|-----------------------|
| Sequence Block | | | Optional | |
| BEĞINS | | | 0 to many allowed | |
| Address1 | String 64 | | | |
| Address2 | String 64 | | | |
| Address3 | String 50 | | | |
| Address4 | String 50 | | | |
| City | String 50 | | | |
| County | String 45 | | | |
| State | String 50 | | | |
| ZipCode | String 10 | | | |
| GPS Coordinates | GPSCoordinatesType | | | Refer to this complex |
| GPS Coordinates | complex type | | | type in Section 5 |
| Urbanization | String 28 | | | |
| Foreign Address | foreignAddressType | | | Refer to this complex |
| ForeignAddress | complex type | | | type in Section 5 |
| Sequence Block | | | | |
| ENDS | | | | |

5.2 Complex Type: basicReturnInfo

| Field | Format | Acceptable Values | Business Rules | Comments |
|-----------------------------|--|-------------------|-------------------------------|---|
| Sequence Block BEGINS | | | Optional 0 to many allowed | |
| Return Code | Numeric String – Length 4 | - | Optional | |
| Return Description | String, Length 260 | - | Required | |
| ContainerErrorWarnin gBlock | containerErrorWarnin gBlockType complex type | - | Optional | Refer to this complex type in Section 5 |
| Sequence Block ENDS | | | | |

5.3 Complex Type: CRIDCreateResponseType

| o.o complex Type. On Doreate (caponac Type | | | | |
|--|--|------------------|----------------|---|
| Field | Format | Acceptable Value | Business Rules | Comments |
| CRIDCreateRespons eType BEGINS | | | | |
| CRID Type | CRIDType String Simple type | - | Optional | Refer to this simple type in Section 6 |
| CRIDStatus Type | CRIDStatus Type String simple type | | Optional | Refer to this simple type in Section 6 |
| CRIDEntry Type | CRIDEntryType complex type | - | Optional | Refer to this complex type in Section 5 |
| Related Permit Publication Data Type | Permit Publication Data Type yesNo simple type | - | Optional | Refer to this simple type in Section 6 |
| Return Info Type | ReturnInfo Type Complex type | - | Optional | Refer to this complex type in Section 5 |
| CRIDCreateRespons eType ENDS | | | | |

5.4 Complex Type: CRIDEntryType

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------------------------------|---|------------------|---|---|
| CRIDEntryType BEGINS | | | | |
| CRID Type | CRIDType simple type | | Optional | Refer to this simple type in Section 6 |
| CompanyName | String 255 | | Required | |
| PermitPublicationDat a | permitPublicationData Type complex type | - | Optional | Refer to this complex type in Section 5 |
| CompanyHQIndicator | yesNo simple type | - | Optional | Refer to this simple type in Section 6 |
| Address | addressType complex type | - | Optional | Refer to this complex type in Section 5 |
| AddressMatch | yesNo simple type | - | Required | Refer to this simple type in Section 6 |
| ApplyingForSelf | yesNo simple type | - | Required | Refer to this simple type in Section 6 |
| LegalAcknowledgeme ntBlock | legalAcknowledgeme ntBlockCRIDtype complex type | - | Conditional; required when ApplyingForSelf is set to "No" | Refer to this complex type in Section 5 |
| CRIDEntryType ENDS | | | | |

5.5 Complex Type: CRIDsRequestedType

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------------------------------|---|------------------|---|---|
| CRIDsRequestedTyp e BEGINS | | | | |
| CRID Type | CRIDType simple type | | Optional | Refer to this simple type in Section 6 |
| CompanyName | String 255 | | Required | |
| Address | addressType complex type | - | Optional | Refer to this complex type in Section 5 |
| PermitPublicationDat a | permitPublicationData Type complex type | - | Optional | Refer to this complex type in Section 5 |
| ApplyingForSelf | yesNo simple type | - | Required | Refer to this simple type in Section 6 |
| LegalAcknowledgeme ntBlock | legalAcknowledgeme ntBlockCRIDtype complex type | - | Conditional; required when ApplyingForSelf is set to "No" | Refer to this complex type in Section 5 |
| CRIDsRequestedTyp e ENDS | | | | |

5.6 Complex Type: CRIDQueryResponseType

| 3.0 Complex Type. On Dade Tynesponse Type | | | | |
|---|---------------------------------|------------------|----------------|---|
| Field | Format | Acceptable Value | Business Rules | Comments |
| midCreateResponseT ype BEGINS | | | | |
| CRIDEntry Type | CRIDEntryType complex type | - | Optional | Refer to this complex type in Section 5 |
| CRID Type | CRIDType String Simple type | - | Optional | Refer to this simple type in Section 6 |
| Return Info Type | ReturnInfo Type Complex type | - | Optional | Refer to this simple type in Section 6 |

| Field | Format | Acceptable Value | Business Rules | Comments |
|--------------------|--------|------------------|----------------|----------|
| midCreateResponseT | | | | |
| ype ENDS | | | | |

5.7 Complex Type: CRIDValidateResponseType

| Field | Format | Acceptable Value | Business Rules | Comments |
|----------------------------------|-------------------------------|------------------|----------------|---|
| midCreateResponseT ype BEGINS | | | | |
| CRIDEntry Type | CRIDEntryType complex type | - | Optional | Refer to this complex type in Section 5 |
| CRID Matches Type | CRIDMatches yesNo Simple Type | | Required | Refer to this simple type in Section 6 |
| Return Info Type | ReturnInfo Type Complex type | - | Optional | Refer to this complex type in Section 5 |
| midCreateResponseT ype ENDS | | | | |

5.8 Complex Type: ForeignAddressType

| Field | Format | Acceptable Values | Business Rules | Comments |
|------------------------|-----------|-------------------|-------------------|----------|
| Sequence Block | | | Optional | |
| BEGINS | | | 0 to many allowed | |
| AddressLine1 | String 50 | | | |
| AddressLine2 | String 50 | | | |
| AddressLine3 | String 50 | | | |
| CountryCode | String 03 | | | |
| Sequence Block ENDS | | | | |

5.9 Complex Type: LegalAknowledgmentBlockCRIDType

| Field | Format | Acceptable Value | Business Rules | Comments |
|---|-------------------|------------------|--|--|
| LegalAcknowledgeme ntBlockCRIDType BEGINS | | | | |
| UnderstandLegalLiabi lityForApplyingForSo meOneElse | yesNo simple type | - | Required | Refer to this simple type in Section 6 |
| AcknowledgeNotifying TheMailOwner | yesNo simple type | - | Required | Refer to this simple type in Section 6 |
| USPSLegalAgreemen t | String | | Required This Declaration pertains to the Mail Service Provider service that allows authorized Mail Service Providers to register with the United States Postal Service (USPS) to receive, apply, and use USPS system identification numbers on behalf of a Mail Owner a. A Mail | - |

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------|--------|------------------|---|----------|
| | | | Service Provider | |
| | | | (MSP), hereafter | |
| | | | known as Mailing | |
| | | | Agent, is a company | |
| | | | or entity that performs | |
| | | | one or more of the | |
| | | | following functions on | |
| | | | behalf of other companies or | |
| | | | organizations: | |
| | | | designs, creates, | |
| | | | prepares, processes, | |
| | | | sorts, or otherwise | |
| | | | prepares postcards, | |
| | | | letters, flats or | |
| | | | packages for | |
| | | | acceptance and | |
| | | | delivery by the Postal | |
| | | | Service b. A Mail | |
| | | | Owner is defined as a | |
| | | | company that has | |
| | | | authorized a Mail | |
| | | | Service Provider to | |
| | | | act as its Mailing | |
| | | | Agent with the USPS, | |
| | | | and to perform | |
| | | | Mailing Services on | |
| | | | its behalf using the | |
| | | | Mail Owner's Mailer | |
| | | | ID/Customer | |
| | | | Registration ID or | |
| | | | other USPS system | |
| | | | identification number in the Mail Owner's | |
| | | | name c. USPS | |
| | | | system identification | |
| | | | numbers include but | |
| | | | are not limited to | |
| | | | Mailer ID (MID) and | |
| | | | Customer | |
| | | | Registration ID | |
| | | | (CRID). A CRID is a | |
| | | | unique number for a | |
| | | | Mail Owner or Mailing | |
| | | | Agent at an address | |
| | | | and is normally | |
| | | | assigned when a Mail | |
| | | | Owner or Mailing | |
| | | | Agent applies online | |
| | | | with the Postal | |
| | | | Service through the | |
| | | | Business Customer | |
| | | | Gateway d. | |
| | | | By/For reflects the | |
| | | | relationship between | |
| | | | the Mail Owner and | |
| | | | Mailing Agent where | |

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------|--------|------------------|---|----------|
| | | | typically the By field | |
| | | | identifies the Mailing | |
| | | | Agent and the For | |
| | | | field identifies the Mail | |
| | | | Owner e. A MID is | |
| | | | a six-digit or nine-digit | |
| | | | unique number which | |
| | | | the USPS assigns to a Mail Owner or | |
| | | | Mailing Agent for use | |
| | | | in the Intelligent Mail | |
| | | | barcodes to identify | |
| | | | the Mail Owner or | |
| | | | Mailing Agent. A MID | |
| | | | is used to send | |
| | | | information to the Mail | |
| | | | Owner or Mailing | |
| | | | Agent associated with | |
| | | | the Mailer ID | |
| | | | regarding Intelligent | |
| | | | Mail mailing and | |
| | | | shipping, and is | |
| | | | normally assigned when a Mail Owner or | |
| | | | Mailing Agent applies | |
| | | | online with the USPS | |
| | | | through the Business | |
| | | | Customer Gateway | |
| | | | f. A Business | |
| | | | Service is defined as | |
| | | | an online business | |
| | | | function accessed | |
| | | | through the Business | |
| | | | Customer Gateway at | |
| | | | gateway.usps.com, | |
| | | | hereafter known as | |
| | | | Business Services g. I, the Mailing | |
| | | | g. I, the Mailing Agent, declare to the | |
| | | | USPS that I have | |
| | | | been authorized by | |
| | | | my Mail Owner(s) to | |
| | | | act as their Mailing | |
| | | | Agent with the USPS | |
| | | | and obtain the | |
| | | | Business Services | |
| | | | requested for | |
| | | | business mailing | |
| | | | matters on their behalf h. The | |
| | | | Mailing Agent | |
| | | | acknowledges that it | |
| | | | has informed its Mail | |
| | | | Owner customer(s), | |
| | | | via electronic or paper | |
| | | | communication, that: - | |
| | | | i. 1. The Mail Owner | |

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------|--------|------------------|---------------------------------------|----------|
| | | | remains responsible | |
| | | | for all actions | |
| | | | performed by its | |
| | | | Mailing Agent with | |
| | | | respect to its Mailer | |
| | | | IDs, CRIDs or other | |
| | | | USPS system | |
| | | | identification numbers | |
| | | | and Business | |
| | | | Services; - j. 2. The | |
| | | | Mail Owner can | |
| | | | obtain details or ask | |
| | | | questions from the | |
| | | | USPS regarding its USPS system | |
| | | | identification numbers | |
| | | | and/or access to their | |
| | | | information online at | |
| | | | gateway.usps.com; | |
| | | | and - k. 3. When the | |
| | | | Delegate | |
| | | | Management option | |
| | | | for an USPS system | |
| | | | identification numbers | |
| | | | has been requested, | |
| | | | the management of | |
| | | | the USPS system | |
| | | | identification numbers | |
| | | | or Business Services | |
| | | | access obtained on | |
| | | | their behalf will be | |
| | | | delegated to the | |
| | | | Mailing Agent | |
| | | | company and that this | |
| | | | delegation may be | |
| | | | revoked by the Mail | |
| | | | Owner at any time I. | |
| | | | The Mailing Agent | |
| | | | declares, that: - m. | |
| | | | 1. It has reviewed | |
| | | | the terms and conditions, as outlined | |
| | | | in the Guide to | |
| | | | Intelligent Mail Letters | |
| | | | and Flats regarding | |
| | | | mailer identification | |
| | | | (By/For) relationship | |
| | | | information with all | |
| | | | Mail Owners for | |
| | | | whom the customer | |
| | | | identification numbers | |
| | | | or business services | |
| | | | have been requested; | |
| | | | and/or - n. It has | |
| | | | reviewed the terms | |
| | | | and conditions, as | |
| | | | outlined in Publication | |

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------|--------|------------------|---|----------|
| Field | Format | Acceptable Value | 199 Intelligent Mail Package Barcode (IMpb) Implementation Guide for Confirmation Services and Electronic Verification System (eVS) Mailers and Publication 205 Electronic Verification System (eVS) Business and Technical Guide regarding use of the CRIDs, MID and other USPS identification numbers; - o. 2. It has advised and provided its Mail Owner the requisite information that is provided by the USPS including but not limited to USPS documentation on products and services defined in the Mailing Standards of the United States Postal Service (Domestic Mail Manual and International Mail Manual), technical specifications and guides, Postal Bulletins and Federal Register Notices; - p. 3. It has provided its Mail Owner the requisite information regarding pricing programs which includes but is not limited to incentive | Comments |
| | | | regarding pricing programs which includes but is not limited to incentive programs, contractual pricing the promotional campaign marketing material; work share discounts policies, participation and eligibility rules as defined in Federal Register Notices filed by Product Classification of the | |
| | | | USPS; and - q. 4. My Mail Owner has | |

| Field | Format | Acceptable Value | Business Rules | Comments |
|---|--------|------------------|--|----------|
| | | | provided this authorization in writing and will produce such authorization upon request to the USPS or the United States Postal Inspection Service (or their agent) r. | |
| LegalAcknowledgeme ntBlockCRIDType ENDS | | | | |

5.10 Complex Type: LegalAknowledgmentBlockMIDType

| Field | Format | Acceptable Value | Business Rules | Comments |
|---|-------------------|------------------|---|--|
| LegalAcknowledgeme ntBlockMIDType BEGINS | | | | |
| UnderstandLegalLiabi lityForApplyingForSo meOneElse | yesNo simple type | - | Required | Refer to this simple type in Section 6 |
| AcknowledgeNotifying TheMailOwner | yesNo simple type | - | Required | Refer to this simple type in Section 6 |
| USPSLegalAgreemen t | String | | Required This Declaration pertains to the Mail Service Provider service that allows authorized Mail Service Providers to register with the United States Postal Service (USPS) to receive, apply, and use USPS system identification numbers on behalf of a Mail Owner a. A Mail Service Provider (MSP), hereafter known as Mailing Agent, is a company or entity that performs one or more of the following functions on behalf of other companies or organizations: designs, creates, prepares, processes, sorts, or otherwise prepares postcards, letters, flats or packages for | - |

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------|--------|------------------|--|----------|
| | | | acceptance and | |
| | | | delivery by the Postal | |
| | | | Service b. A Mail | |
| | | | Owner is defined as a | |
| | | | company that has | |
| | | | authorized a Mail | |
| | | | Service Provider to | |
| | | | act as its Mailing | |
| | | | Agent with the USPS, | |
| | | | and to perform | |
| | | | Mailing Services on | |
| | | | its behalf using the Mail Owner's Mailer | |
| | | | ID/Customer | |
| | | | Registration ID or | |
| | | | other USPS system | |
| | | | identification number | |
| | | | in the Mail Owner's | |
| | | | name c. USPS | |
| | | | system identification | |
| | | | numbers include but | |
| | | | are not limited to | |
| | | | Mailer ID (MID) and | |
| | | | Customer | |
| | | | Registration ID | |
| | | | (CRID). A CRID is a | |
| | | | unique number for a | |
| | | | Mail Owner or Mailing | |
| | | | Agent at an address | |
| | | | and is normally | |
| | | | assigned when a Mail | |
| | | | Owner or Mailing | |
| | | | Agent applies online | |
| | | | with the Postal | |
| | | | Service through the Business Customer | |
| | | | Gateway d. | |
| | | | By/For reflects the | |
| | | | relationship between | |
| | | | the Mail Owner and | |
| | | | Mailing Agent where | |
| | | | typically the By field | |
| | | | identifies the Mailing | |
| | | | Agent and the For | |
| | | | field identifies the Mail | |
| | | | Owner e. A MID is | |
| | | | a six-digit or nine-digit | |
| | | | unique number which | |
| | | | the USPS assigns to | |
| | | | a Mail Owner or | |
| | | | Mailing Agent for use | |
| | | | in the Intelligent Mail | |
| | | | barcodes to identify the Mail Owner or | |
| | | | | |
| | | | Mailing Agent. A MID is used to send | |
| | | | information to the Mail | |
| | | | inionnation to the Mall | İ |

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------|--------|------------------|---|----------|
| Field | Format | Acceptable Value | Owner or Mailing Agent associated with the Mailer ID regarding Intelligent Mail mailing and shipping, and is normally assigned when a Mail Owner or Mailing Agent applies online with the USPS through the Business Customer Gateway f. A Business Service is defined as an online business function accessed through the Business Customer Gateway at gateway.usps.com, hereafter known as Business Services g. I, the Mailing Agent, declare to the USPS that I have been authorized by my Mail Owner(s) to act as their Mailing Agent with the USPS and obtain the Business Services requested for business mailing matters on their behalf h. The Mailing Agent acknowledges that it has informed its Mail Owner customer(s), via electronic or paper communication, that: - i. 1. The Mail Owner remains responsible for all actions performed by its Mailing Agent with respect to its Mailer IDs, CRIDs or other USPS system identification numbers and Business | Comments |
| | | | Services; - j. 2. The Mail Owner can obtain details or ask questions from the USPS regarding its | |
| | | | USPS system identification numbers | |

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------|--------|------------------|--------------------------|----------|
| | | | and/or access to their | |
| | | | information online at | |
| | | | gateway.usps.com; | |
| | | | and - k. 3. When the | |
| | | | Delegate | |
| | | | Management option | |
| | | | for an USPS system | |
| | | | identification numbers | |
| | | | has been requested, | |
| | | | the management of | |
| | | | the USPS system | |
| | | | identification numbers | |
| | | | or Business Services | |
| | | | access obtained on | |
| | | | their behalf will be | |
| | | | delegated to the | |
| | | | Mailing Agent | |
| | | | company and that this | |
| | | | delegation may be | |
| | | | revoked by the Mail | |
| | | | Owner at any time I. | |
| | | | The Mailing Agent | |
| | | | declares, that: - m. | |
| | | | 1. It has reviewed | |
| | | | the terms and | |
| | | | conditions, as outlined | |
| | | | in the Guide to | |
| | | | Intelligent Mail Letters | |
| | | | and Flats regarding | |
| | | | mailer identification | |
| | | | (By/For) relationship | |
| | | | information with all | |
| | | | Mail Owners for | |
| | | | whom the customer | |
| | | | identification numbers | |
| | | | or business services | |
| | | | have been requested; | |
| | | | and/or - n. It has | |
| | | | reviewed the terms | |
| | | | and conditions, as | |
| | | | outlined in Publication | |
| | | | 199 Intelligent Mail | |
| | | | Package Barcode | |
| | | | (IMpb) | |
| | | | Implementation Guide | |
| | | | for Confirmation | |
| | | | Services and | |
| | | | Electronic Verification | |
| | | | System (eVS) Mailers | |
| | | | and Publication 205 | |
| | | | Electronic Verification | |
| | | | System (eVS) | |
| | | | Business and | |
| | | | Technical Guide | |
| | | | regarding use of the | |
| | | | CRIDs, MID and other | |
| | | | USPS identification | |

| Field | Format | Acceptable Value | Business Rules | Comments |
|------------------------|--------|------------------|--|----------|
| LegalAcknowledgeme | | | numbers; - o. 2. It has advised and provided its Mail Owner the requisite information that is provided by the USPS including but not limited to USPS documentation on products and services defined in the Mailing Standards of the United States Postal Service (Domestic Mail Manual and International Mail Manual), technical specifications and guides, Postal Bulletins and Federal Register Notices; - p. 3. It has provided its Mail Owner the requisite information regarding pricing programs which includes but is not limited to incentive programs, contractual pricing the promotional campaign marketing material; work share discounts policies, participation and eligibility rules as defined in Federal Register Notices filed by Product Classification of the USPS; and - q. 4. My Mail Owner has provided this authorization in writing and will produce such authorization upon request to the USPS or the United States Postal Inspection Service (or their agent) r. | |
| ntBlockMIDType ENDS | | | | |

| 5.11 Complex Type | 5.11 Complex Type: LegalAknowledgmentBlockMSPSType | | | | |
|---|--|------------------|---|--|--|
| Field | Format | Acceptable Value | Business Rules | Comments | |
| LegalAcknowledgeme ntBlockMSPSType BEGINS | | | | | |
| UnderstandLegalLiabi lityForApplyingForSo meOneElse | yesNo simple type | - | Required Default = No | Refer to this simple type in Section 6 | |
| AcknowledgeNotifying TheMailOwner | yesNo simple type | - | Required | Refer to this simple type in Section 6 | |
| USPSLegalAgreemen t | String | | Required This Declaration pertains to the Mail Service Provider service that allows authorized Mail Service Providers to register with the United States Postal Service (USPS) to receive, apply, and use USPS system identification numbers on behalf of a Mail Owner a. A Mail Service Provider (MSP), hereafter known as Mailing Agent, is a company or entity that performs one or more of the following functions on behalf of other companies or organizations: designs, creates, prepares, processes, sorts, or otherwise prepares postcards, letters, flats or packages for acceptance and delivery by the Postal Service b. A Mail Owner is defined as a company that has authorized a Mail Service Provider to act as its Mailing Agent with the USPS, and to perform Mailing Services on its behalf using the Mail Owner's Mailer ID/Customer Registration ID or other USPS system identification number | | |

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------|--------|------------------|---|----------|
| | | | in the Mail Owner's | |
| | | | name c. USPS | |
| | | | system identification | |
| | | | numbers include but | |
| | | | are not limited to | |
| | | | Mailer ID (MID) and | |
| | | | Customer Registration ID | |
| | | | (CRID). A CRID is a | |
| | | | unique number for a | |
| | | | Mail Owner or Mailing | |
| | | | Agent at an address | |
| | | | and is normally | |
| | | | assigned when a Mail | |
| | | | Owner or Mailing | |
| | | | Agent applies online | |
| | | | with the Postal | |
| | | | Service through the | |
| | | | Business Customer | |
| | | | Gateway d. | |
| | | | By/For reflects the | |
| | | | relationship between | |
| | | | the Mail Owner and | |
| | | | Mailing Agent where | |
| | | | typically the By field | |
| | | | identifies the Mailing | |
| | | | Agent and the For field identifies the Mail | |
| | | | Owner e. A MID is | |
| | | | a six-digit or nine-digit | |
| | | | unique number which | |
| | | | the USPS assigns to | |
| | | | a Mail Owner or | |
| | | | Mailing Agent for use | |
| | | | in the Intelligent Mail | |
| | | | barcodes to identify | |
| | | | the Mail Owner or | |
| | | | Mailing Agent. A MID | |
| | | | is used to send | |
| | | | information to the Mail | |
| | | | Owner or Mailing | |
| | | | Agent associated with | |
| | | | the Mailer ID | |
| | | | regarding Intelligent | |
| | | | Mail mailing and shipping, and is | |
| | | | normally assigned | |
| | | | when a Mail Owner or | |
| | | | Mailing Agent applies | |
| | | | online with the USPS | |
| | | | through the Business | |
| | | | Customer Gateway | |
| | | | f. A Business | |
| | | | Service is defined as | |
| | | | an online business | |
| | | | function accessed | |
| | | | through the Business | |

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------|--------|------------------|--|----------|
| Field | Format | Acceptable Value | Customer Gateway at gateway.usps.com, hereafter known as Business Services g. I, the Mailing Agent, declare to the USPS that I have been authorized by my Mail Owner(s) to act as their Mailing Agent with the USPS and obtain the Business Services requested for business mailing matters on their behalf h. The Mailing Agent acknowledges that it has informed its Mail Owner customer(s), via electronic or paper communication, that: -i. 1. The Mail Owner remains responsible for all actions performed by its Mailing Agent with respect to its Mailer IDs, CRIDs or other USPS system identification numbers and Business Services; - j. 2. The Mail Owner can obtain details or ask questions from the USPS regarding its USPS system identification numbers and/or access to their information online at gateway.usps.com; and - k. 3. When the Delegate Management option for an USPS system identification numbers has been requested, | Comments |
| | | | has been requested, the management of the USPS system identification numbers or Business Services access obtained on their behalf will be | |
| | | | delegated to the Mailing Agent | |

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------|--------|------------------|--|----------|
| | | | company and that this | |
| | | | delegation may be | |
| | | | revoked by the Mail | |
| | | | Owner at any time I. | |
| | | | The Mailing Agent | |
| | | | declares, that: - m. 1. It has reviewed | |
| | | | the terms and | |
| | | | conditions, as outlined | |
| | | | in the Guide to | |
| | | | Intelligent Mail Letters | |
| | | | and Flats regarding | |
| | | | mailer identification | |
| | | | (By/For) relationship | |
| | | | information with all | |
| | | | Mail Owners for | |
| | | | whom the customer | |
| | | | identification numbers | |
| | | | or business services | |
| | | | have been requested; | |
| | | | and/or - n. It has | |
| | | | reviewed the terms | |
| | | | and conditions, as | |
| | | | outlined in Publication | |
| | | | 199 Intelligent Mail | |
| | | | Package Barcode | |
| | | | (IMpb) | |
| | | | Implementation Guide | |
| | | | for Confirmation Services and | |
| | | | Electronic Verification | |
| | | | System (eVS) Mailers | |
| | | | and Publication 205 | |
| | | | Electronic Verification | |
| | | | System (eVS) | |
| | | | Business and | |
| | | | Technical Guide | |
| | | | regarding use of the | |
| | | | CRIDs, MID and other | |
| | | | USPS identification | |
| | | | numbers; - o. 2. It | |
| | | | has advised and | |
| | | | provided its Mail | |
| | | | Owner the requisite | |
| | | | information that is | |
| | | | provided by the USPS | |
| | | | including but not limited to USPS | |
| | | | documentation on | |
| | | | products and services | |
| | | | defined in the Mailing | |
| | | | Standards of the | |
| | | | United States Postal | |
| | | | Service (Domestic | |
| | | | Mail Manual and | |
| | | | International Mail | |
| | | | Manual), technical | |

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------------------------|--------|------------------|--|----------|
| LegalAcknowledgeme | | | specifications and guides, Postal Bulletins and Federal Register Notices; - p. 3. It has provided its Mail Owner the requisite information regarding pricing programs which includes but is not limited to incentive programs, contractual pricing the promotional campaign marketing material; work share discounts policies, participation and eligibility rules as defined in Federal Register Notices filed by Product Classification of the USPS; and - q. 4. My Mail Owner has provided this authorization in writing and will produce such authorization upon request to the USPS or the United States Postal Inspection Service (or their agent). – r. | |
| ntBlockMSPSType ENDS | | | | |

5.12 Complex Type: MIDCreateResponseType

| Field | Format | Acceptable Value | Business Rules | Comments |
|---|--|------------------|----------------|---|
| midCreateResponseT ype BEGINS | | | | |
| MID Type | MIDType Complex type | - | Optional | Refer to this complex type in Section 5 |
| MIDStatus Type | String simple type | | Optional | Refer to this simple type in Section 6 |
| MIDEntry Type | MIDEntryType complex type | - | Optional | Refer to this complex type in Section 5 |
| Related Permit Publication Data Type | Permit Publication Data Type yesNo simple type | - | Optional | Refer to this simple type in Section 6 |
| Return Info Type | ReturnInfo Type Complex type | | Optional | Refer to this complex type in Section 5 |
| midCreateResponseT ype ENDS | | | | |

5.13 Complex Type: MIDEntryType

| Field | Format | Acceptable Value | Business Rules | Comments |
|-------------------------------|--|------------------|--|---|
| midEntryType BEGINS | | | | |
| MID | MID Type Complex Type | | Optional | Refer to this complex type in Section 5 |
| CustomerCRID | CRIDType simple type | - | Required | Refer to this simple type in Section 6 |
| CustomerName | String | | Optional | |
| PermitPublicationData | permitPublicationData Type complex type | - | Optional | Refer to this complex type in Section 5 |
| CompanyHQIndicator | yesNo simple type | - | Optional | Refer to this simple type in Section 6 |
| AddressType | AddressType complex type | | Optional | Refer to this complex type in Section 5 |
| SequenceNumber | integer | | | |
| ApplyingForSelf | yesNo simple type | - | Required | Refer to this simple type in Section 6 |
| LegalAcknowledgmen t Block | legalAcknowledgeme ntBlockMIDType complex type | - | Conditional; Required when ApplyingForSelf is "No" | Refer to this complex type in Section 5 |
| midEntryType ENDS | | | | |

5.14 Complex Type: MIDQueryResponseType

| 5.14 Complex Type: Milb Query Nesponse Type | | | | |
|---|---------------------------|------------------|----------------|---|
| Field | Format | Acceptable Value | Business Rules | Comments |
| midCreateResponseT ype BEGINS | | | | |
| MID Type | MIDType Complex type | - | Optional | Refer to this complex type in Section 5 |
| MIDStatus Type | String simple type | | Optional | Refer to this simple type in Section 6 |
| MIDEntry Type | MIDEntryType complex type | - | Optional | Refer to this complex type in Section 5 |
| Return Info Type | Return Info simple type | | Optional | Refer to this simple type in Section 6 |
| midCreateResponseT ype ENDS | | | | |

5.15 Complex Type: MIDType

| Field | Format | Acceptable Value | Business Rules | Comments |
|----------------|---------------------------|------------------|----------------|--|
| MIDType BEGINS | | | | |
| MID6 | mailerID6Type simple type | | Required | Refer to this simple type in Section 6 |
| OR | | | | |
| MID9 | mailerID9Type simple type | | Required | Refer to this simple type in Section 6 |
| MIDType ENDS | | | | |

5.16 Complex Type: MIDValidateResponseType

| Field | Format | Acceptable Value | Business Rules | Comments |
|---------------------------------|------------------------------|------------------|----------------|---|
| MIDValidateRespons eType BEGINS | | | | |
| MIDEntry Type | MIDEntryType complex type | - | Optional | Refer to this complex type in Section 5 |
| MIDMatches Type | MIDMatches yesNo simple type | | Required | Refer to this simple type in Section 6 |
| Return Info Type | Return Info simple type | | Optional | Refer to this simple type in Section 6 |
| MIDValidateRespons eType ENDS | | | | |

5.17 Complex Type: permitPublicationDataType

| Field | Format | Acceptable Values | Business Rules | Comments |
|-----------------------------------|-------------------------------|-------------------|--|--|
| permitPublicationData Type BEGINS | | | | |
| Choice Block BEGINS | - | - | Either PermitNumber, PermitType, PermitZip4 OR Publication Number is required | - |
| Sequence Block BEGINS | | | | |
| Permit Number | String, 8 | - | Required, when providing Permit Number and Permit Zip4 data | - |
| Permit Type | permitTypeType simple type | - | Required | Refer to this simple type in Section 6 |
| Permit Zip4 | Numeric String, 9 | - | Required when providing Permit Number and Permit Zip 4 data | Refer to this simple type in Section 6 |
| Sequence Block ENDS | | | | |
| Publication Number | String, 8 | - | Either provide Permit Number, Permit Type 4 and optional Permit Type OR this field. | - |
| Choice Block ENDS | | | | |

| Field | Format | Acceptable Values | Business Rules | Comments |
|-----------------------|--------|-------------------|----------------|----------|
| permitPublicationData | | | | |
| Type ENDS | | | | |

5.18 Complex Type: SubmittingParty, participantIDType

| Field | Format | Acceptable Values | Business Rules | Comments |
|--------------------|-------------------------------------|-------------------|--|--|
| MailerID6 | mailID6Type simple type | | Not required (attribute) Either MailerID6 or MailerID9 can be provided, not both | Refer to this simple type in Section 6 |
| MailerID9 | mailerID9Type | | Not required (attribute) Either MailerID6 or MailerID9 can be provided, not both | Refer to this simple type in Section 6 |
| CRID | CRIDType | | Not required (attribute), Either CRID or MID can be provided for authorization | Refer to this simple type in Section 6 |
| SchedulerID | String, 12 | | Optional | |
| MaildatUserLicense | userLicenseCodeTyp e simple type | | Optional | Refer to this simple type in Section 6 |
| ShippingAgentID | String 12 | - | Optional | - |
| ReceivingAgentID | String 12 | - | Optional | - |

5.19 Complex Type: SubmittingSoftware

| Field | Format | Acceptable Values | Business Rules | Comments |
|--------------|--------|-------------------|----------------|--|
| SoftwareName | String | | Required | |
| Vendor | String | | Required | |
| Version | String | | Required | |
| ApprovalDate | Date | YYYY-MM-DD | Optional | Changed the type to 'Date' based on errata |
| ApprovalKey | String | | Optional | |

5.20 Complex Type: VerificationErrorType

| Field | Format | Acceptable Value | Business Rules | Comments |
|-----------------------|------------------|------------------|-------------------|----------|
| Sequence Block | | | Optional | |
| BEGINS | | | 0 to many allowed | |
| VerificationErrorCode | Numeric String 4 | | Required | |
| VerificationError | String 260 | | Optional | |
| Description | Offing 200 | | Optional | |
| Sequence Block | | | | |
| ENDS | | | | |

6. Simple Types Data Structure

6.1 simpleType: CRIDStatusType

| Tag | CRIDStatusType |
|-------------|----------------|
| Base | xs:string |
| enumeration | New |
| enumeration | Existing |

6.2 simpleType: CRIDType

| Tag | CRIDType |
|-----------|-----------|
| Base | xs:string |
| maxLength | 15 |
| minLength | 1 |
| pattern | ([0-9])* |

6.3 simpleType: EnrollingForSelf

| Tag | EnrollingForSelf | |
|------|--------------------|--|
| Base | mailxml_base:yesNo | |

6.4 simpleType: mailerID6Type

| Tag | mailerID6Type | |
|------|-------------------|--|
| Base | mailxml_base:ns06 | |

6.5 simpleType: mailerID9Type

| Tag | mailerID9Type |
|------|-------------------|
| Base | mailxml_base:ns09 |

6.6 simpleType: MIDorCRIDRequestType

| Tag | MIDorCRIDRequestType |
|-------------|----------------------|
| Base | xs:string |
| enumeration | Create |
| enumeration | Query |
| enumeration | Validate |

6.7 simpleType: mIDStatusType

| Tag | mIDStatusType |
|-------------|---------------|
| Base | xs:string |
| enumeration | New |
| enumeration | Existing |

6.8 simpleType: ns04

| Tag | ns04 |
|---------|-----------|
| Base | xs:string |
| pattern | [0-9]{4} |

6.9 simpleType: ns05

| 0.0 0p.0yp | |
|------------|-----------|
| Tag | ns05 |
| Base | xs:string |
| pattern | [0-9]{5} |

6.10 simpleType: ns09

| Tag | ns09 |
|---------|-----------|
| Base | xs:string |
| pattern | [0-9]{9} |

6.11 simpleType: permitTypeType

| orr omporpormer | | |
|-----------------|--|--|
| permitTypeType | | |
| xs:string | | |
| PI | | |
| MT | | |
| PC | | |
| BR | | |
| PE | | |
| GH | | |
| OI | | |
| OM | | |
| PP | | |
| • | | |
| | | |

6.12 simpleType: s12

| Tag | s12 |
|------------|-----------|
| Base | xs:string |
| maxLength | 12 |
| minLength | 1 |
| whiteSpace | preserve |

6.13 simpleType: s40

| Tag | s40 |
|------------|-----------|
| Base | xs:string |
| maxLength | 40 |
| minLength | 1 |
| whiteSpace | preserve |

6.14 simpleType: s50

| Tag | s50 |
|------------|-----------|
| Base | xs:string |
| maxLength | 50 |
| minLength | 1 |
| whiteSpace | preserve |

6.15 simpleType: s64

| Tag | s64 |
|------------|-----------|
| Base | xs:string |
| maxLength | 64 |
| minLength | 1 |
| whiteSpace | preserve |

6.16 simpleType: s255

| Tag | S255 |
|-----------|-----------|
| Base | xs:string |
| maxLength | 255 |

| Tag | S255 |
|------------|----------|
| minLength | 1 |
| whiteSpace | preserve |

6.17 simpleType: s260

| Tag | s260 |
|------------|-----------|
| Base | xs:string |
| maxLength | 260 |
| minLength | 1 |
| whiteSpace | preserve |

7. WSDL Reference Information

Note: USPS no longer supports string-type WSDLs.

The WSDL specification is posted on RIBBS $^{\otimes}$ and can be downloaded from the following location: Web Service Description Language (WSDL) Specification

The above RIBBS® URL provides WSDLs for both the Test Environment for Mailers (TEM) and the production environment. Use this link to access the most current versions of WSDLs.

8. Change History Archives

These are the changes to Mail.XML MID-CRID 16.0-R18 Edition 2 Change 1

| Date | Section # | Title | Description |
|---------|-----------|-------|---|
| 7/30/14 | Various | N/A | Updated cover page, footer, and roadmap to reflect Edition 2 publication date of August 1 and release deployment date of November 2014. |

These are the changes to Mail.XML MID-CRID 16.0-R18 Edition 2 Change 0

| Date | Section # | Title | Description |
|---------|-----------|-------|---------------------------------|
| 6/25/14 | Various | N/A | Updated cover page, footer, TOC |
| | | | |

These are the changes to Mail.XML MID-CRID 16.0-R18 Edition 1 Change 1

| Date | Section # | Title | Description |
|---------|-----------|-------|--|
| 5/21/14 | Various | N/A | Updated for release date change from July to August 2014 |

These are the changes to Mail.XML MID-CRID 16.0-R18 Edition 1 Change 0

| Date | Section # | Title | Description |
|---------|-----------|---------------------|---|
| 5/14/14 | 1.5 | Roadmap of Mail.XML | Added column for October 2014 release; removed July 2013 column |
| 5/14/14 | Various | N/A | Updated cover page, footer, table of contents |

These are the changes to Mail.XML MID-CRID 16.0-R17 Edition 2 Change 2

| Date | Section # | Title | Description |
|-------|-----------|------------------------------|--|
| 2/26/ | 14 1.9 | Profiles Management Features | Modified wording to remove references to "unassociated" Full Service ACS profiles |

These are the changes to Mail.XML MID-CRID 16.0-R17 Edition 2 Change 1

| Date | Section # | Title | Description |
|---------|-----------|--------------------------------------|---|
| 2/24/14 | 1.6 | Roadmap of Mail.XML | Removed April 2013 column from table |
| 2/25/14 | 6 | Simple Types Data Structure | Added s255 to Mailxml_base (CR 1480) |
| 2/25/14 | 2.1.3 | USPS CRID Create Request Overview | Expanded CompanyName from string 40 to string 255 in table |
| 2/25/14 | 4.3 | USPSCRIDCreateValidateRequest | Expanded CompanyName from string 40 to string 255 and corrected message name in field description table |
| 2/25/14 | 4.4 | USPSCRIDCreateValidateResponse | Corrected order of ReturnInfo and RelatedPermitPublicationData |
| | | | Expanded CompanyName from string 40 to string 255 in table and corrected rule designation from optional to required |
| 2/25/14 | 5.4 | Complex Type CRIDEntryType | Corrected CRID Type in table to reference simple type definition in sec 6 |
| | | | Added CRIDsRequestedType with CompanyName |
| 2/25/14 | 5.5 | Complex Type CRIDsRequestedType | s255 |
| 2/25/14 | 7 | WSDL Reference Information | Renamed section to remove reference to XSD |

These are the changes to Mail.XML MID-CRID 16.0-R17 Edition 2 Change 0

| Date | Section # | Title | Description |
|-------------------------|-------------------|-------------|--|
| 2/18/14 3.4 Fault Codes | | Fault Codes | Replaced fault code table with updated codes (Table 3-3) |
| | Simple Types Data | | |
| 2/18/14 | 6 | Structure | Corrected alphabetization |
| | Cover page, | | Updated date, edition |
| | footer, Table of | | Updated Table of Contents and Index after section |
| 2/18/14 | Contents, Index | N/A | modifications |

These are the changes to Mail.XML MID-CRID 16.0-R17 Edition 1 Change 2

| Date | Section # | Title | Description |
|---------|-----------|------------|---------------------------------------|
| 1/16/14 | N/A | Intro page | Corrected ACS designation from ® to ™ |

These are the changes to Mail.XML MID-CRID 16.0-R17 Edition 1 Change 1

| Date | Section # | Title | Description |
|---------|-------------------|--|---|
| 1/14/14 | Header, Footer | Entire Document | Updated publication date and edition, minor spelling and grammar edits, updated Table of Contents and Index |
| 1/14/14 | 4.1 | USPSMIDCreateValidateRequest | Updated Address Information in Business Rules Updated Field Description Table: Removed Address1, Address2, City, State, and ZipCode from MIDEntryType Added AddressType complex type to MIDEntryType |
| 1/15/14 | 4.3 | USPSCRIDCreateValidateRequest | Updated Address Information in Business Rules |
| 1/15/14 | 5.0 | Mail.XML 16.0A Complex and Attribute Group Definitions | Added AddressType and ForeignAddressType complex type definitions |
| 1/15/14 | 2.2.3 | USPS MID Create Validate Request Overview | Added missing MIDEntry elements to table 2-2 |

These are the changes to Mail.XML-14.0A-R16 Edition 3 Change 0

| Date | Section # | Title | Description |
|---------|-----------|-----------------|--------------------------------------|
| | Header, | | |
| 11/5/13 | Footer | Entire Document | Updated publication date and edition |

These are the changes to Mail.XML -14.0A-R16 Edition 1 Change 0

| Date | Section # | Title | Description |
|------------|-----------|-----------------------------|--|
| 07/16/2013 | All | Entire Document | Derived from Mail.XML 14.0A MID-CRID Version 3.0 |
| 08/23/2013 | 6 | Simple Data Type Structures | Updated simpleType: MIDorCRIDRequestType |

These are the changes from Mail.XML 14.0A MID-CRID Version 2.0 to Mail.XML 14.0A MID-CRID Version 3.0

| Date | Section # | Title | Description |
|--------|---------------|---|---|
| 7/3/13 | 5.10 | MIDEntryType | Added MID element to MIDEntryType |
| 7/3/13 | 5.3 | CRIDEntryType | Added CRID element to CRIDEntryType |
| 7/3/13 | 5.2, 5.4, 5.5 | CRIDCreateResponseType, CRIDQueryResponseType, CRIDValidateResponseType | Added CRIDCreateResponseType, CRIDQueryResponseType, CRIDValidateResponseType |

| 7/3/13 | 5.9, 5.11, 5.13 | MIDCreateResponseType, MIDQueryResponseType, MIDValidateResponseType | Added MIDCreateResponseType, MIDQueryResponseType, MIDValidateResponseType |
|---------|-------------------------------|--|--|
| 5/28/13 | 6.0 Section 6 Simple Types | MIDorCRIDRequestType | MIDorCRIDRequestType was added. |
| 5/28/13 | Header and Footer | Header and Footer | Document Version updated |
| 5/21/13 | Header and Footer | Header and Footer | Document Version updated |
| 5/21/13 | 2.1.1, 2.1.2 | Preconditions | Wording updated |

These are the changes from Mail.XML 14.0A MID-CRID Version 1.0 to Mail.XML 14.0A MID-CRID Version 2.0

| Date | Section # | Title | Description |
|---------|-----------|-------------------------------|---|
| 3/20/13 | 1.6 | Hyperlinks | Made XML and XSD URL's hyperlinks |
| 3/20/13 | 1.8 | Alignment | Adjusted alignment |
| 3/20/13 | 1.9 | Bullets | Removed extra bullet points in front of text |
| 3/20/13 | 4.1,4.3 | Verbiage | Updated wording of Legal Acknowledgment Block in 4.3 to the same as in 4.1 and added closing quotation mark |
| 3/7/13 | 5.2 | CRIDEntryType | Updated CRIDEntryType to make CompanyName and Address optional |
| 3/1/13 | All | Header and Footer | Updated Header and Footer |
| 3/1/13 | 4.2 | USPSMIDCreateValidateResponse | Flipped the RelatedPermitPublicationData and ReturnInfo fields. |

These are the changes from Mail.XML 12.0B MID-CRID Version 7.0 to Mail.XML 14.0A MID-CRID Version 1.0

| Date | Section # | Title | Description |
|---------|-----------|-----------------------------------|--|
| 2/20/13 | 4 | Data Structure and Business Rules | Updated the MID_CRID messages in the section 4 to conform to those in the mailxml_id_14.0A.xsd |
| 2/20/13 | 1.5 | Roadmap Table | Updated roadmap table to indicate version that is scheduled to retire in April |
| 2/20/13 | | Table of Contents | Removed unwanted table of contents at the end of document |
| 2/20/13 | All | Footer | Updated version date in footer |
| 1/31/13 | 4.3 | USPSCRIDCreateValidateResponse | Updated CRID,CRIDstatus,and CRIDEntry in USPSCRIDCreateAccept from Required to Optional |
| 1/31/13 | 4.2 | USPSMIDCreateValidateResponse | Updated MID, MIDstatus, and MIDEntry in USPSMIDCreateAccept from Required to Optional |

INDEX

| | Α |
|---------------|------------------------------|
| authorization | 39 |
| | С |
| CRID | 12, 14, 15, 16, 18, 39 |
| | F |
| feedback | 12, 14, 15, 18 |
| | М |
| Mail.XML | 3, 8, 9, 10, 12, 20 |
| MID | 12, 15 12, 14, 15, 18, 39 |
| | Р |
| | 12, 16, 38 |

| PostalOne! | 12, 14, 15, 18 | | | | |
|--|----------------------|--|--|--|--|
| S | | | | | |
| Sequencespecification | 13 | | | | |
| SubmittingPartySubmittingSoftware | | | | | |
| U | | | | | |
| USPSUSPSCRIDCreateRequestUSPSCRIDCreateResponseUSPSMIDCreateResponse | 15, 16, 18 15, 18 | | | | |
| w | | | | | |
| WSDL | 43 | | | | |